

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

REACH Registration Number: 01-2119463588-24-XXXX
EC No: 919-284-0**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**Reagents and laboratory chemicals
Only for laboratory and analysis purposes.**Uses advised against**

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH
	ACD
Street:	Stempelstraße 6
Place:	D-47167 Duisburg
Telephone:	0203/5194-0
E-mail:	info@analytichem.de
Contact person:	Abteilung Produktsicherheit
E-mail:	produktsicherheit@analytichem.de
Internet:	www.analytichem.de
Responsible Department:	Abteilung Produktsicherheit

Telefax: 0203/5194-290

Telephone: 0203/5194-107/117

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

No data available

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**Carc. 2; H351
STOT SE 3; H336
Asp. Tox. 1; H304
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008**

Signal word: Danger

Pictograms:



according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 2 of 13

Hazard statements

H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing and eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.
 P405 Store locked up.
 P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	Hydrocarbons, C10, aromatics, > 1% naphthalene			
	Carc. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H351 H336 H304 H411 EUH066			
91-20-3	naphthalene			
	202-049-5	601-052-00-2		
	Flam. Sol. 1, Carc. 2, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H228 H351 H302 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	Hydrocarbons, C10, aromatics, > 1% naphthalene		
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 10650 mg/kg		
91-20-3	202-049-5	naphthalene	10 - < 15 %
	inhalation: LC50 = > 77,7 mg/l (vapours); dermal: LD50 = > 16000 mg/kg; oral: LD50 = 710 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 3 of 13

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Headache
May cause drowsiness or dizziness.
Dizziness
Gastrointestinal complaints
Irritant
Repeated exposure may cause skin dryness or cracking.
Anaesthetic state
Pneumonia
Dermatitis

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration hazard

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂) Carbon monoxide
In case of warming:
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 4 of 13

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

In case of warming:

Vapours may form explosive mixtures with air.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 5 of 13

ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
91-20-3	Naphthalene	10	50		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
Hydrocarbons, C10, aromatics, > 1% naphthalene					
	Worker DNEL, long-term		dermal	systemic	12,5 mg/kg bw/day
	Consumer DNEL, long-term		inhalation	systemic	32 mg/m ³
	Consumer DNEL, long-term		dermal	systemic	7,5 mg/kg bw/day
	Consumer DNEL, long-term		oral	systemic	7,5 mg/kg bw/day
	Worker DNEL, long-term		inhalation	systemic	151 mg/m ³
91-20-3	naphthalene				
	Worker DNEL, long-term		inhalation	systemic	25 mg/m ³
	Worker DNEL, long-term		inhalation	local	25 mg/m ³
	Worker DNEL, long-term		dermal	systemic	3,57 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 6 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
91-20-3	naphthalene	
Freshwater		0,0024 mg/l
Freshwater (intermittent releases)		0,02 mg/l
Marine water		0,0024 mg/l
Freshwater sediment		0,0672 mg/kg
Marine sediment		0,0672 mg/kg
Micro-organisms in sewage treatment plants (STP)		2,9 mg/l
Soil		0,0533 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation : KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<>) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 7 of 13

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear
Odour:	like: aromatic hydrocarbons
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	182-206 °C
Flammability:	No data available
Lower explosion limits:	0,9 vol. %
Upper explosion limits:	7 vol. %
Flash point:	67 °C
Auto-ignition temperature:	448 °C
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic: (at 20 °C)	1,33 mm ² /s
Water solubility:	practically insoluble
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,8 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 8 of 13

Oxidizing properties
No data available

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	100%
Solid content:	0%
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming:
Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
Hydrocarbons, C10, aromatics, > 1% naphthalene					
	oral	LD50 mg/kg	10650 Rat	Study report (1991)	OECD Guideline 420
	dermal	LD50 mg/kg	> 2000 Rabbit	Study report (1995)	OECD Guideline 402
91-20-3	naphthalene				
	oral	LD50 mg/kg	710 Mouse	FUND. APPL. TOXICOL 4: 406-419 (1984) (1)	OECD Guideline 401
	dermal	LD50 mg/kg	> 16000 Rat	Study report (1980)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 mg/l	> 77,7 Rat	Study report (1985)	other: EPA TSCA

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

slightly irritant but not relevant for classification.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Hydrocarbons, C10, aromatics, > 1% naphthalene; naphthalene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C10, aromatics, > 1% naphthalene)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Headache

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 10 of 13

May cause drowsiness or dizziness.

Dizziness

Gastrointestinal complaints

Irritant

Repeated exposure may cause skin dryness or cracking.

Anaesthetic state

Pneumonia

Dermatitis

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
Hydrocarbons, C10, aromatics, > 1% naphthalene						
	Acute algae toxicity	ErC50 mg/l	> 1 - < 3	72 h Pseudokirchneriella subcapitata	Study report (1993)	OECD Guideline 201
	Fish toxicity	NOEC mg/l	0,487	28 d Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	0,851	21 d Daphnia magna	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
91-20-3	naphthalene					
	Acute fish toxicity	LC50 mg/l	1,6	96 h Oncorhynchus mykiss	Arch. Environm. Contam. Toxicol. 11, 487	OECD Guideline 203
	Acute algae toxicity	ErC50 ca. 0,4 - ca. 0,5 mg/l	ca. 0,4 - ca. 0,5 mg/l	72 h Skeletonema costatum	Mar Environ Res 11, 183-200 (1984)	Aquatic toxicity of water soluble fracti
	Acute crustacea toxicity	EC50 mg/l	2,16	48 h Daphnia magna	Transactions of the American Fisheries S	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,37	40 d Oncorhynchus kisutch	Trans. Am. Fish. Soc. 110:430-436, 1981	Coho salmon fry were exposed for 40 days
	Crustacea toxicity	NOEC mg/l	0,59	125 d Daphnia pulex	Can. J. Fish. Aquat. Sci. 39: 830 - 834	During chronic studies in closed static

12.2. Persistence and degradability

Poorly biodegradable.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
91-20-3	naphthalene	3,4

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 11 of 13

BCF

CAS No	Chemical name	BCF	Species	Source
91-20-3	naphthalene	36,5 - 168	Cyprinus carpio	http://www.safe.nite

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Hydrocarbons, C10, aromatics, > 1% naphthalene)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Hydrocarbons, C10, aromatics, > 1% naphthalene)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 12 of 13

Classification code: M6
Special Provisions: 274 335 375 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Hydrocarbons, C10, aromatics,> 1% naphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Special Provisions: 274, 335, 969
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Hydrocarbons, C10, aromatics,> 1% naphthalene)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9
Special Provisions: A97 A158 A197
Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1
IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
Danger releasing substance: Hydrocarbons, C10, aromatics,> 1% naphthalene

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent Naphtha S Distillation range 180 - 210 °C Tax-free energy product! Must not be used as fuel

Revision: 18.09.2025

Product code: 28354

Page 13 of 13

SECTION 16: Other information

Abbreviations and acronyms

Flam. Sol. 1: Flammable solids, hazard category 1
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Carc. 2: Carcinogenicity, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1

Relevant H and EUH statements (number and full text)

H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users