

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Substance name: Petroleum benzine
 REACH Registration Number: 01-2119475133-43-XXXX
 CAS No: 64742-49-0
 EC No: 265-151-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
 Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
 Street: Rua de Júlio Dinis 676 7º
 Place: N-4050-320 Porto
 Telephone: +351 226002917
 E-mail: info@analytichem.com
 Contact person: SDS service department
 E-mail: SDS@analytichem.com
 Internet: www.analytichem.com
 Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Belgium NV
 Street: Industriezone "De Arend" 2
 Place: B-8210 Zedelgem
 Telephone: +32 50 28 83 20
 E-mail: info.be@analytichem.com
 Contact person: SDS service department
 E-mail: SDS@analytichem.com
 Responsible Department: AnalytiChem:
 EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
 EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
 EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
 UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
 USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
 Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
 Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 2 of 11

1.4. Emergency telephone number: +44 20 3807 3798 (CHEMTREC)

Further Information

No data available

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Repr. 2; H361
Skin Irrit. 2; H315
STOT SE 3; H336
STOT RE 2; H373
Asp. Tox. 1; H304
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Petroleum benzine

Signal word: Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves/protective clothing and eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 3 of 11

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-49-0	Petroleum benzene			100 %
	265-151-9		01-2119475133-43-XXXX	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361 H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

Further Information

No data available

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove person to fresh air and keep comfortable for breathing. Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂)

Foam

Extinguishing powder

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 4 of 11

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 5 of 11

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid exposure - obtain special instructions before use.
Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Provide adequate ventilation. Do not breathe vapour.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

National regulations

Further information on storage conditions

Keep container tightly closed and dry.
Keep cool. Protect from sunlight.
storage temperature: < +30°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

Observe in addition any national regulations!

8.2. Exposure controls

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 6 of 11

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn (EN ISO 374)

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Gasoline
Odour threshold:	No data available
Melting point/freezing point:	-100 °C
Boiling point or initial boiling point and boiling range:	40-60 °C
Flammability:	No data available
Lower explosion limits:	0,8 vol. %
Upper explosion limits:	8 vol. %
Flash point:	-21 °C
Auto-ignition temperature:	250 °C
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	practically insoluble

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 7 of 11

Solubility in other solvents

No data available

Dissolution rate:

No data available

Partition coefficient n-octanol/water:

No data available

Dispersion stability:

No data available

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

0,653 g/cm³

Relative density:

No data available

Bulk density:

No data available

Relative vapour density:

No data available

Particle characteristics:

No data available

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

Sustained combustibility

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles

Rubber articles

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 8 of 11

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes****Acute toxicity**

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility or the unborn child. (Petroleum benzene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Petroleum benzene)

Organs affected: central nervous system

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Petroleum benzene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Avoid exposure - obtain special instructions before use.

Further information

Irritant

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

SECTION 12: Ecological information**12.1. Toxicity**

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 9 of 11

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of UK REACH.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	UN 1268
<u>14.2. UN proper shipping name:</u>	PETROLEUM DISTILLATES, N.O.S.
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	640D ADR664
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 1268
<u>14.2. UN proper shipping name:</u>	PETROLEUM DISTILLATES, N.O.S.
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Classification code:	F1
Special Provisions:	640D

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 10 of 11

Limited quantity: 1 L

Excepted quantity: E2

Marine transport (IMDG)**14.1. UN number or ID number:** UN 1268**14.2. UN proper shipping name:** PETROLEUM DISTILLATES, N.O.S.**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Special Provisions: -

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:** UN 1268**14.2. UN proper shipping name:** PETROLEUM DISTILLATES, N.O.S.**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3

Special Provisions: A3

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: Naphtha (petroleum), hydrotreated light

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

Other applicable information

No data available

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints 100%

and varnishes:

Information according to Directive E2 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Additional information: P5c

Additional information

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing

Petroleum ether 40-60 a.r.; Petroleum ether 40-60 a.r.

Revision: 19.11.2025

Product code: AC11.00347

Page 11 of 11

mothers.

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 3,4,5,7,8,9,12,13,15.

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Irrit. 2: Skin irritation, hazard category 2

Repr. 2: Reproductive toxicity, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users