

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Toluene/ethanol mixture pure

UFI: 6VG2-93JK-8002-K805

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem GmbH
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
E-mail: info@analytichem.de
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.de
Responsible Department: AnalytiChem
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

1.4. Emergency telephone number:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 2 of 15

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Repr. 2; H361d
Skin Irrit. 2; H315
STOT SE 3; H336
STOT RE 2; H373
Asp. Tox. 1; H304
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling
toluene

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves/protective clothing and eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 3 of 15

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			50 - < 55 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			
64-17-5	ethanol			45 - < 50 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	50 - < 55 %
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		
64-17-5	200-578-6	ethanol	45 - < 50 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off immediately all contaminated clothing.

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth thoroughly with water.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 4 of 15

Irritant

Aspiration hazard

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 5 of 15

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

- Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
- Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep in a cool, well-ventilated place.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

- national regulations

Further information on storage conditions

- Keep cool. Protect from sunlight.

7.3. Specific end use(s)

- Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 6 of 15

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
64-17-5	Ethyl alcohol	1000	-		STEL (15 min)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
108-88-3	toluene			
	Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
	Worker DNEL, acute	inhalation	systemic	384 mg/m ³
	Worker DNEL, long-term	inhalation	local	192 mg/m ³
	Worker DNEL, acute	inhalation	local	384 mg/m ³
	Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	226 mg/m ³
	Consumer DNEL, long-term	inhalation	local	56,5 mg/m ³
	Consumer DNEL, acute	inhalation	local	226 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
64-17-5	ethanol			
	Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 7 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 8 of 15

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	>35 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	<21 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents not determined	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 9 of 15

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Self-ignition temperature

Solid: not applicable

Gas: not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

various plastics

10.6. Hazardous decomposition products

in case of fire, see:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 10 of 15

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
108-88-3	toluene					
	oral	LD50 mg/kg	5580	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 mg/kg	> 5000	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 mg/l	28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403
64-17-5	ethanol					
	oral	LD50 mg/kg	10470	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 mg/l	124,7	Rat	Study report (1980)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

There are no data available on the mixture itself.

Further information

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 11 of 15

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 > 433 mg/l	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 11,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC 1,39 mg/l	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC > 400 mg/l	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC 0,74 mg/l	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 12 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
64-17-5	ethanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3

Classification code:

F1

Special Provisions:

274 601 640D

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 1993

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 13 of 15

14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, ethanol; ethyl alcohol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	No
----------------------------	----

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 14 of 15

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.
Water hazard class (D):	3 - highly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Irrit. 2: Eye irritation, hazard category 2
Repr. 2: Reproductive toxicity, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Repr. 2; H361d	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing,

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Toluene/ethanol mixture pure

Revision: 10.12.2025

Product code: AC11.00451

Page 15 of 15

the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)