

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Titration solvent for Bromide index dete

UFI: 8QPD-G1TX-700S-FRC6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: N-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Belgium NV
Street: Industriezone "De Arend" 2
Place: B-8210 Zedelgem
Telephone: +32 50 28 83 20
E-mail: info.be@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+44 20 3807 3798 (CHEMTREC)

1.4. Emergency telephone number:

Further Information

inapplicable, this product is a mixture REACH registration number see section 3

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 2 of 17

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226
Met. Corr. 1; H290
Carc. 2; H351
Acute Tox. 4; H332
Acute Tox. 4; H302
Skin Corr. 1B; H314
Eye Dam. 1; H318
STOT SE 1; H370
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

acetic acid
dichloromethane
methanol

Signal word:

Danger

Pictograms:**Hazard statements**

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

Special labelling

For use in industrial installations only.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 3 of 17

3.2. Mixtures**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-19-7	acetic acid			70 - < 75 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr. 1A, Eye Dam. 1; H226 H314 H318			
75-09-2	dichloromethane			15 - < 20 %
	200-838-9	602-004-00-3	01-2119480404-41	
	Carc. 2, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H351 H315 H319 H336			
67-56-1	methanol			10 - < 15 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-19-7	200-580-7	acetic acid	70 - < 75 %
		oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25	
75-09-2	200-838-9	dichloromethane	15 - < 20 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	
67-56-1	200-659-6	methanol	10 - < 15 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection!
Call a physician immediately.

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 4 of 17

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

corrosive

Irritant

Cough

Dyspnoea

Respiratory complaints

Dizziness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Hydrogen chloride (HCl)

Phosgene

Sulphur oxides

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 5 of 17

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Collect in closed and suitable containers for disposal.
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use extractor hood (laboratory).
Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Use personal protection equipment.
Provide adequate ventilation. Avoid contact with skin, eyes and clothes.
Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.
In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 6 of 17

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Store in a well-ventilated place. Keep container tightly closed.

Corrosive to metals.

Hints on joint storage

Take national regulations into account.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	WEL
		20	50		STEL (15 min)	WEL
75-09-2	Dichloromethane	100	353		TWA (8 h)	WEL
		200	706		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
75-09-2	Dichloromethane	carbon monoxide	30 ppm	end-tidal breath	Post shift

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 7 of 17

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64-19-7	acetic acid			
Worker DNEL, long-term		inhalation	local	25 mg/m³
Worker DNEL, acute		inhalation	local	25 mg/m³
Consumer DNEL, long-term		inhalation	local	25 mg/m³
Consumer DNEL, acute		inhalation	local	25 mg/m³
75-09-2	dichloromethane			
Worker DNEL, long-term		inhalation	systemic	353 mg/m³
Worker DNEL, acute		inhalation	systemic	706 mg/m³
Worker DNEL, long-term		dermal	systemic	12 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	88,3 mg/m³
Consumer DNEL, acute		inhalation	systemic	353 mg/m³
Consumer DNEL, long-term		dermal	systemic	5,82 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,06 mg/kg bw/day
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m³
Worker DNEL, long-term		inhalation	systemic	260 mg/m³
Worker DNEL, acute		inhalation	systemic	260 mg/m³
Worker DNEL, long-term		inhalation	local	260 mg/m³
Worker DNEL, acute		inhalation	local	260 mg/m³
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m³
Consumer DNEL, long-term		inhalation	local	50 mg/m³
Consumer DNEL, acute		inhalation	local	50 mg/m³
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 8 of 17

PNEC values

CAS No	Substance	
Environmental compartment		Value
64-19-7	acetic acid	
Freshwater		3,058 mg/l
Freshwater (intermittent releases)		30,58 mg/l
Marine water		0,306 mg/l
Freshwater sediment		11,36 mg/kg
Marine sediment		1,136 mg/kg
Micro-organisms in sewage treatment plants (STP)		85 mg/l
Soil		0,47 mg/kg
75-09-2	dichloromethane	
Freshwater		0,31 mg/l
Freshwater (intermittent releases)		0,27 mg/l
Marine water		0,031 mg/l
Freshwater sediment		2,57 mg/kg
Marine sediment		0,26 mg/kg
Micro-organisms in sewage treatment plants (STP)		26 mg/l
Soil		0,33 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following specification (test according to EN 374):

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 9 of 17

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	40 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	35 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	< 2
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 10 of 17

Vapour pressure:	No data available
Density:	1,06785 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: No data available

Self-ignition temperature

Solid: No data available

Gas: No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

No data available:

Viscosity / dynamic: No data available

Flow time: No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity**10.1. Reactivity**

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Corrosive to metals.

10.2. Chemical stability

Protect against:

Heat

10.3. Possibility of hazardous reactions

Ammonia (NH₃), Amines, Nitrogen oxides (NO_x), Alkali (lye), Fluorine, Alkali metals Alkaline earth metal, metals, Powdered metals, Methanol, Light metal, Ketone, Oxidising agent, strong

10.4. Conditions to avoid

Protect against:

Heat

10.5. Incompatible materials

Rubber articles

plastics

Metal

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 11 of 17

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes

Toxicokinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Harmful if inhaled.

Harmful if swallowed.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

ATEmix calculated

ATE (oral) 997,3 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 4,987 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-19-7	acetic acid				
	oral	LD50 3310 mg/kg	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194)	The sodium salt of acetic acid was admin
75-09-2	dichloromethane				
	oral	LD50 > 2000 mg/kg	Rat	Other company data (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Other company data (1988)	OECD Guideline 402
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (dichloromethane)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 12 of 17

Aspiration hazard

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs. (Pulmonary oedema Pneumonia)

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards**Other information**

There are no data available on the mixture itself.

Further information

corrosive

Irritant

Cough

Dyspnoea

Respiratory complaints

Dizziness

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 13 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-19-7	acetic acid					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Skeletonema costatum	Study report (2005)	ISO 10253
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202
75-09-2	dichloromethane					
	Acute fish toxicity	LC50 193 mg/l	96 h	Pimephales promelas	Bull Environ Contam Toxicol 20, 344-352	According to test methods described by t
	Acute crustacea toxicity	EC50 27 mg/l	48 h	Daphnia magna	Study report (1979)	According EPA publication
	Fish toxicity	NOEC 357 mg/l	8 d	Pimephales promelas	Bull Environ Contam Toxicol 39, 869-876 (other: ASTM E729-80
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17
75-09-2	dichloromethane	1,25
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch
75-09-2	dichloromethane	> 0,91 - < 7,9		Washington, DC, US E
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 14 of 17

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	83
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+3
Classification code:	CF1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 15 of 17

14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+3
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2920
14.2. UN proper shipping name:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8+3
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 59, Entry 69, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): H3 STOT SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

Additional information: P5c

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,9,12.

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 16 of 17

Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1
Flam. Liq. 2: Flammable liquids, hazard category 2
Flam. Liq. 3: Flammable liquids, hazard category 3
Acute Tox. 3: Acute toxicity, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Skin Corr. 1A: Skin corrosion, sub-category 1A
Skin Corr. 1B: Skin corrosion, sub-category 1B
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Carc. 2: Carcinogenicity, hazard category 2
STOT SE 1: Specific target organ toxicity - single exposure, hazard category 1
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Met. Corr. 1; H290	On basis of test data
Carc. 2; H351	Calculation method
Acute Tox. 4; H332	Calculation method
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H290 May be corrosive to metals.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H302+H332 Harmful if swallowed or if inhaled.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H370 Causes damage to organs (eyes, central nervous system).
H370 Causes damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing,

Titration solvent for Bromide index dete

Revision: 18.03.2025

Product code: AC11.00564

Page 17 of 17

the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)