

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Butanol-(1), HPLC grade

REACH Registration Number: 01-2119484630-38-XXXX
CAS No: 71-36-3
Index No: 603-004-00-6
EC No: 200-751-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: N-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Belgium NV
Street: Industriezone "De Arend" 2
Place: B-8210 Zedelgem
Telephone: +32 50 28 83 20
E-mail: info.be@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

1.4. Emergency telephone number:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 2 of 13

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226
Acute Tox. 4; H302
Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 3; H335
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula:	CH ₃ (CH ₂) ₃ OH
Molecular weight:	74,12 g/mol

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 3 of 13

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
71-36-3	butanol			100 %
	200-751-6	603-004-00-6	01-2119484630-38-XXXX	
	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
71-36-3	200-751-6	butanol	100 %
	dermal: LD50 = ca. 3430 mg/kg; oral: LD50 = ca. 2292 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes.

Irritant

corrosive

Vapours may cause drowsiness and dizziness.

Cough

Dyspnoea

Cardiac arrhythmias

Circulatory collapse

Vomiting

Inebriation

Dizziness

Anaesthetic state

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 4 of 13

Respiratory complaints

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO₂)

Foam

Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 5 of 13

basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

national regulations

Further information on storage conditions

Protect from sunlight.

minimum storage temperature +5°C

maximum storage temperature +30°C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 6 of 13

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
71-36-3	Butan-1-ol	20	-		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
71-36-3	butanol			
Worker DNEL, long-term		inhalation	local	310 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	55,357 mg/m ³
Consumer DNEL, long-term		inhalation	local	155 mg/m ³
Consumer DNEL, long-term		dermal	systemic	3,125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,562 mg/kg bw/day

PNEC values

CAS No	Substance	Value
71-36-3	butanol	
Freshwater		0,082 mg/l
Freshwater (intermittent releases)		2,25 mg/l
Marine water		0,008 mg/l
Freshwater sediment		0,324 mg/kg
Marine sediment		0,032 mg/kg
Micro-organisms in sewage treatment plants (STP)		2476 mg/l
Soil		0,017 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 7 of 13

supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 730 Camatril® Velours

Suitable material: NBR (Nitrile rubber) 0,4 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear fire resistant or flame retardant clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: A

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Alcohol
Odour threshold:	No data available
Melting point/freezing point:	-89 °C
Boiling point or initial boiling point and boiling range:	119 °C
Flammability:	No data available
Lower explosion limits:	1,4 vol. %
Upper explosion limits:	11,3 vol. %
Flash point:	35 °C
Auto-ignition temperature:	355 °C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 8 of 13

Decomposition temperature:	No data available
pH-Value (at 20 °C):	7 (70 g/l)
Viscosity / kinematic:	No data available
Water solubility: (at 20 °C)	66 g/l
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	10 hPa
Vapour pressure:	No data available
Density:	0,81 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

Sustained combustibility

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

100%

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:

2,95 mPa·s

(at 20 °C)

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 9 of 13

10.3. Possibility of hazardous reactions

Oxidising agent
Alkali metals
Alkaline earth metal,
Acid chlorides, inorganic
Reducing agent
Aluminium
chromium trioxide

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

rubber
Plastic articles
various plastics

10.6. Hazardous decomposition products

in case of fire, see:
SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

No data available

Acute toxicity

Harmful if swallowed.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
71-36-3	butanol				
	oral	LD50 ca. 2292 mg/kg	Rat	Study report (1967)	OECD Guideline 401
	dermal	LD50 ca. 3430 mg/kg	Rabbit	Study report (1951)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (butanol)
May cause drowsiness or dizziness. (butanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 10 of 13

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards**Endocrine disrupting properties**

No data available

Other information

Vomiting

Observe risk of aspiration if vomiting occurs.

Liver and kidney damage

Inhalation effect: Damage to the respiratory tract.

Further information

Risk of serious damage to eyes.

Irritant

corrosive

Vapours may cause drowsiness and dizziness.

Cough

Dyspnoea

Cardiac arrhythmias

Circulatory collapse

Vomiting

Inebriation

Dizziness

Anaesthetic state

Respiratory complaints

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
71-36-3	butanol					
	Acute fish toxicity	LC50 1376 mg/l	96 h	Pimephales promelas	Study report (1998)	OECD Guideline 203
	Acute algae toxicity	ErC50 225 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1998)	OECD Guideline 201
	Acute crustacea toxicity	EC50 1328 mg/l	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202
	Crustacea toxicity	NOEC 4,1 mg/l	21 d	Daphnia magna	Study report (1996)	OECD Guideline 211

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 11 of 13

98 %; 28 d

Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
71-36-3	butanol	10

BCF

CAS No	Chemical name	BCF	Species	Source
71-36-3	butanol	3,16		QSAR (2017)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1120
14.2. UN proper shipping name:	BUTANOLS
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1120
--------------------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 12 of 13

14.2. UN proper shipping name:	BUTANOLS
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1120
14.2. UN proper shipping name:	BUTANOLS
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	223
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1120
14.2. UN proper shipping name:	BUTANOLS
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,15.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Butanol-(1), HPLC grade

Revision: 07.07.2025

Product code: AC11.00726

Page 13 of 13

Abbreviations and acronyms

Flam. Liq. 3: Flammable liquids, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.