

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Potassium hydroxide 0.1 mol/l in Ethanol

UFI: RUYE-P0FY-000P-A416

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Reagents and laboratory chemicals  
Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet**

**Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: N-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
Street: Industriezone "De Arend" 2  
Place: B-8210 Zedelgem  
Telephone: +32 50 28 83 20  
E-mail: info.be@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Responsible Department: AnalytiChem:  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333  
+44 20 3807 3798 (CHEMTREC)

**1.4. Emergency telephone number:**

**Further Information**

inapplicable, this product is a mixture REACH registration number see section 3

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 2 of 14

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225

Met. Corr. 1; H290

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

potassium hydroxide

**Signal word:** Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 3 of 14

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-17-5	ethanol			85 - < 90 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
1310-58-3	potassium hydroxide			< 1 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6	ethanol	85 - < 90 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		
1310-58-3	215-181-3	potassium hydroxide	< 1 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Self-protection of the first aider

**After inhalation**

Provide fresh air.

**After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

**After ingestion**

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

corrosive

Irritant

Cough

Dyspnoea

Dizziness

The product causes narcotic-like effects.

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 4 of 14

Inebriation

Vomiting

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquid.

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

Beware of reignition.

**5.3. Advice for firefighters**

Remove persons to safety. Do not inhale explosion and combustion gases.

Avoid contact with skin, eyes and clothes.

In case of fire: Wear self-contained breathing apparatus.

Use water spray jet to protect personnel and to cool endangered containers.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Suppress gases/vapours/mists with water spray jet.

Move undamaged containers from immediate hazard area if it can be done safely.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 5 of 14

basements in higher concentration.

Danger of explosion

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Take national regulations into account.

**Further information on storage conditions**

Vapours may form explosive mixtures with air.

storage temperature +15°C - +25°C

## Potassium hydroxide 0.1 mol/l in Ethanol

Revision: 18.11.2025

Product code: AC15.00467

Page 6 of 14

**7.3. Specific end use(s)**

Laboratory use Laboratory chemical

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	WEL

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>	
Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>	
Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day	
1310-58-3	potassium hydroxide			
Worker DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>	
Consumer DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>	

**PNEC values**

CAS No	Substance	Value
64-17-5	ethanol	
Freshwater	0,96 mg/l	
Freshwater (intermittent releases)	2,75 mg/l	
Marine water	0,79 mg/l	
Freshwater sediment	3,6 mg/kg	
Marine sediment	2,9 mg/kg	
Secondary poisoning	380 mg/kg	
Micro-organisms in sewage treatment plants (STP)	580 mg/l	
Soil	0,63 mg/kg	

**8.2. Exposure controls****Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: goggles.

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 7 of 14

**Hand protection**

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) with the following specification (test according to EN 374):

By long-term hand contact

Recommended glove articles: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles KCL 720 Camapren®

Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellow
Odour:	like: Ethanol
Odour threshold:	No data available
Melting point/freezing point:	~114 °C
Boiling point or initial boiling point and boiling range:	~78 °C
Flammability:	not applicable
Lower explosion limits:	3,5 vol. %
Upper explosion limits:	15 vol. %
Flash point:	12 °C
Auto-ignition temperature:	425 °C
Decomposition temperature:	not determined
pH-Value:	alkaline
Viscosity / kinematic:	No data available
Water solubility:	Soluble in: Water
Solubility in other solvents	
not determined	

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 8 of 14

Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	59 hPa
Vapour pressure:	No data available
Density:	~0,827 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	not determined
Particle characteristics:	No data available

**9.2. Other information****Information with regard to physical hazard classes**

## Explosive properties

Vapours can form explosive mixtures with air.

## Sustained combustibility:

Sustained combustibility

## Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

## Oxidizing properties

Not oxidising.

**Other safety characteristics**

## Evaporation rate:

not determined

## Solvent separation test:

No data available

## Solvent content:

No data available

## Solid content:

not determined

## Sublimation point:

No data available

## Softening point:

No data available

## Pour point:

No data available

## No data available:

## Viscosity / dynamic:

1,2 mPa·s

(at 20 °C)

## Flow time:

No data available

**Further Information**

May be corrosive to metals.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Highly flammable.

Vapours can form explosive mixtures with air.

May be corrosive to metals.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent, Hydrogen peroxide, Nitric acid, Alkali metals, Alkaline earth metal

Chlorine, Fluorine, silver, permanganates, e.g. potassium permanganate

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.



**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 9 of 14

**10.5. Incompatible materials**

Glass  
Plastic articles  
Metal

**10.6. Hazardous decomposition products**

Hazardous combustion products  
In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.  
If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).  
Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.  
Inhalation effect: Damage to the respiratory tract.  
Resorption (by inhalation)

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol				
	oral	LD50 10470 mg/kg	Rat	Study report (1976)	OECD Guideline 401
	inhalation (4 h) vapour	LC50 124,7 mg/l	Rat	Study report (1980)	OECD Guideline 403
1310-58-3	potassium hydroxide				
	oral	LD50 333 mg/kg	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.  
Serious eye damage/eye irritation: Causes serious eye irritation.  
Risk of serious damage to eyes.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 10 of 14

**Aspiration hazard**

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards****Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

corrosive

Irritant

Cough

Dyspnoea

Dizziness

The product causes narcotic-like effects.

Inebriation

Vomiting

Risk of serious damage to eyes.

Corneal opacity.

**Further information**

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77

**BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

There are no data available on the mixture itself.

**Further information**

Avoid release to the environment.

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.

Send to a physico-chemical treatment facility under observation of official regulations.

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 12 of 14

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Special Provisions:	A3

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 13 of 14

Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	363
IATA-max. quantity - Cargo:	5 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive  
2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,9.

**Abbreviations and acronyms**

Met. Corr. 1: Corrosive to metals, hazard category 1

Flam. Liq. 2: Flammable liquids, hazard category 2

Acute Tox. 4: Acute toxicity, hazard category 4

Skin Corr. 1A: Skin corrosion, sub-category 1A

Skin Irrit. 2: Skin irritation, hazard category 2

Eye Dam. 1: Serious eye damage, hazard category 1

Eye Irrit. 2: Eye irritation, hazard category 2

ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Potassium hydroxide 0.1 mol/l in Ethanol**

Revision: 18.11.2025

Product code: AC15.00467

Page 14 of 14

**Classification for mixtures and used evaluation method**

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Skin Irrit. 2; H315	
Eye Irrit. 2; H319	

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

**Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*