

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 1 of 16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Eriochrome black T - Buffer solution

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet**Details of the supplier of the safety data sheet**

Company name:	AnalytiChem Services, Unipessoal, Lda
Street:	Rua de Júlio Dinis 676 7º
Place:	N-4050-320 Porto
Telephone:	+351 226002917
E-mail:	info@analytichem.com
Contact person:	SDS service department
E-mail:	SDS@analytichem.com
Internet:	www.analytichem.com
Responsible Department:	SDS service department

Supplier or manufacturer details

Company name:	AnalytiChem Belgium NV
Street:	Industriezone "De Arend" 2
Place:	B-8210 Zedelgem
Telephone:	+32 50 28 83 20
E-mail:	info.be@analytichem.com
Contact person:	SDS service department
E-mail:	SDS@analytichem.com
Responsible Department:	AnalytiChem: EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20 EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200 EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848 UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500 USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378 Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701 Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333 +44 20 3807 3798 (CHEMTREC)

1.4. Emergency telephone number:**Further Information**

No data available

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 2 of 16

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Met. Corr. 1; H290
Skin Corr. 1B; H314
Eye Dam. 1; H318
STOT SE 3; H335 H336
Aquatic Acute 1; H400
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

"propan-2-ol; isopropyl alcohol; isopropanol"
Ammonia

Signal word: Danger

Pictograms:

**Hazard statements**

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-aminoethanol. May produce an allergic reaction.

Precautionary statements

P260	Do not breathe mist/vapours/spray.
P264	Wash hands and face thoroughly after handling.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 3 of 16

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"			65 - < 70 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
1336-21-6	Ammonia			5 - < 10 %
	215-647-6	007-001-01-2	01-2119488876-14	
	Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411			
12125-02-9	ammonium chloride			1 - < 5 %
	235-186-4	017-014-00-8	01-2119487950-27	
	Acute Tox. 4, Eye Irrit. 2; H302 H319			
141-43-5	2-aminoethanol			< 1 %
	205-483-3	603-030-00-8	01-2119486455-28	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, STOT SE 3; H332 H312 H302 H314 H318 H317 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1336-21-6	215-647-6	Ammonia	5 - < 10 %
	inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10		
12125-02-9	235-186-4	ammonium chloride	1 - < 5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1410 mg/kg		
141-43-5	205-483-3	2-aminoethanol	< 1 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2504 mg/kg; oral: LD50 = ca. 1515 mg/kg STOT SE 3; H335: >= 5 - 100		

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures**General information**

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 4 of 16

Protect uninjured eye.

After ingestion

If swallowed, immediately drink: Water

Do NOT induce vomiting.

Do not allow a neutralisation agent to be drunk.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns.

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide

Carbon monoxide

Nitrogen oxides (NOx)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

Heating causes rise in pressure with risk of bursting.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Vapours can form explosive mixtures with air.

May be corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

To follow: Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 5 of 16

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Explosion risk.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use.

Handle and open container with care.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Do not breathe dust/fume/gas/mist/vapours/spray.

Provide adequate ventilation.

Use extractor hood (laboratory).

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Advice on general occupational hygiene

Keep away from: Food and feedingstuffs

When using do not eat, drink, smoke, sniff.

Provide eye shower and label its location conspicuously

In the immediate working surroundings there must be: Emergency shower installed

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 6 of 16

Requirements for storage rooms and vessels

Keep container tightly closed.
Corrosive to metals.
Unsuitable container/equipment material: Metal
Protect against: Radiant heat.

Hints on joint storage

Take national regulations into account. /National regulations

Further information on storage conditions

Store in a dry place.
Store in a well-ventilated place.

7.3. Specific end use(s)

The product is intended for research, analysis and scientific education.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-43-5	2-Aminoethanol	1	2.5		TWA (8 h)	WEL
		3	7.6		STEL (15 min)	WEL
7664-41-7	Ammonia, anhydrous	25	18		TWA (8 h)	WEL
		35	25		STEL (15 min)	WEL
12125-02-9	Ammonium chloride, fume	-	10		TWA (8 h)	WEL
		-	20		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 7 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	DNEL type			
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"			
	Worker DNEL, long-term	inhalation	systemic	500 mg/m ³
	Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
1336-21-6	Ammonia			
	Worker DNEL, long-term	inhalation	systemic	47,6 mg/m ³
	Worker DNEL, acute	inhalation	systemic	47,6 mg/m ³
	Worker DNEL, long-term	inhalation	local	14 mg/m ³
	Worker DNEL, acute	inhalation	local	36 mg/m ³
	Worker DNEL, long-term	dermal	systemic	6,8 mg/kg bw/day
	Worker DNEL, acute	dermal	systemic	6,8 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	23,8 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	23,8 mg/m ³
	Consumer DNEL, long-term	inhalation	local	2,8 mg/m ³
	Consumer DNEL, acute	inhalation	local	7,2 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	68 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	68 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	6,8 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	6,8 mg/kg bw/day
12125-02-9	ammonium chloride			
	Worker DNEL, long-term	inhalation	systemic	33,5 mg/m ³
	Worker DNEL, long-term	dermal	systemic	190 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	9,9 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	114 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	11,4 mg/kg bw/day
141-43-5	2-aminoethanol			
	Worker DNEL, long-term	inhalation	local	3,3 mg/m ³
	Worker DNEL, long-term	dermal	systemic	1 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	local	2 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	0,24 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	3,75 mg/kg bw/day

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 8 of 16

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-63-0 "propan-2-ol; isopropyl alcohol; isopropanol"		
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
1336-21-6	Ammonia	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,007 mg/l
Marine water		0,001 mg/l
12125-02-9	ammonium chloride	
Freshwater		1,2 mg/l
Freshwater (intermittent releases)		1,2 mg/l
Marine water		11,2 mg/l
Micro-organisms in sewage treatment plants (STP)		16,2 mg/l
Soil		0,163 mg/kg
141-43-5	2-aminoethanol	
Freshwater		0,085 mg/l
Freshwater (intermittent releases)		0,028 mg/l
Marine water		0,009 mg/l
Freshwater sediment		0,434 mg/kg
Marine sediment		0,043 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,037 mg/kg

Additional advice on limit values

Observe in addition any national regulations!

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaustion at critical locations.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 9 of 16

mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing. Flame-retardant protective clothing . Wear anti-static footwear and clothing
When handling with chemical substances, protective clothing with CE-labels including the four control digits must
be worn.

Take off immediately all contaminated clothing and wash it before reuse .

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	black
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-89 °C
Boiling point or initial boiling point and boiling range:	82 °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	12 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	11-12
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,82 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours can form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

No data available

Solid:

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 10 of 16

Gas: No data available

Oxidizing properties

Oxidizing

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

No data available: No data available

Viscosity / dynamic: No data available

Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Vapours can form explosive mixtures with air.

Corrosive to metals.

10.2. Chemical stability

Protect against: Radiant heat.

10.3. Possibility of hazardous reactions

Oxidising agent

Acid

10.4. Conditions to avoid

Radiant heat.

10.5. Incompatible materials

Metal

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 5000 mg/kg; ATE (dermal) > 2000 mg/kg

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 11 of 16

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
1336-21-6	Ammonia					
	oral	LD50 mg/kg	350	Rat	Journal of Industrial Hygiene and Toxicology	OECD Guideline 401
	inhalation (1 h) vapour	LC50 mg/l	4230	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity
12125-02-9	ammonium chloride					
	oral	LD50 mg/kg	1410	Rat	Other company data (1983)	other: not mentioned
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2010)	EU Method B.3
141-43-5	2-aminoethanol					
	oral	LD50 mg/kg	ca. 1515	Rat	Study report (1966)	OECD Guideline 401
	dermal	LD50 mg/kg	2504	Rabbit	Study report (1988)	OECD Guideline 402
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains 2-aminoethanol. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Ammonia)

May cause drowsiness or dizziness. ("propan-2-ol; isopropyl alcohol; isopropanol")

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 12 of 16

Endocrine disrupting properties

No data available

Other information

No data available

Further information

No data available

SECTION 12: Ecological information**12.1. Toxicity**

Very toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 13 of 16

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"					
	Acute fish toxicity	LC50 10000 mg/l	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203
1336-21-6	Ammonia					
	Acute fish toxicity	LC50 0,75 - 3,4 mg/l	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705-	Assessment of acute toxicity in the fath
	Acute crustacea toxicity	EC50 101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986)	other: ASTM E729-80
	Fish toxicity	NOEC 1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980)	OECD Guideline 210
12125-02-9	ammonium chloride					
	Acute fish toxicity	LC50 209 mg/l	96 h	Cyprinus carpio	Indian J. Environ. Health, 17, 140-146,	other: E03-05:APHA, AWWA & WPCF
	Acute crustacea toxicity	EC50 101 mg/l	48 h	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: ASTM E729-80
	Fish toxicity	NOEC 11,8 mg/l	28 d	Pimephales promelas	Env. Tox. Chem. 5, 437-442 (1986) (1986)	other: - American Society for Testing an
	Algae toxicity	NOEC 26,8 mg/l	10 d	Navicula sp.	Mar. Biol. 43(4), 307-315, (1977) (1977)	no data
	Crustacea toxicity	NOEC 14,6 mg/l	21 d	Daphnia magna	Env. Tox. Chem. 5, 443-447 (1986) (1986)	other: not mentioned
	Acute bacteria toxicity	EC50 1618 mg/l ()	0,5 h	activated sludge, domestic	Study report (1988)	OECD Guideline 209
141-43-5	2-aminoethanol					
	Acute fish toxicity	LC50 349 mg/l	96 h	Cyprinus carpio	Study report (1997)	other: Directive 92/69/EEC, C.1.
	Acute algae toxicity	ErC50 2,8 mg/l	72 h	Pseudokirchneriella subcapitata	unpublished (1997)	OECD Guideline 201
	Acute crustacea toxicity	EC50 65 mg/l	48 h	Daphnia magna	Study report (1997)	EU Method C.2
	Fish toxicity	NOEC 1,24 mg/l	41 d	Oryzias latipes	unpublished (2008)	OECD Guideline 210
	Crustacea toxicity	NOEC 0,85 mg/l	21 d	Daphnia magna	unpublished (1997)	other: OECD 202 "Daphnia sp., Acute Immo

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 14 of 16

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"	0,05
1336-21-6	Ammonia	-1,38
141-43-5	2-aminoethanol	-2,3

BCF

CAS No	Chemical name	BCF	Species	Source
141-43-5	2-aminoethanol	2,3		SAR and QSAR in Envi

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

Explosion risk.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Send to a physico-chemical treatment facility under observation of official regulations .

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

<u>14.1. UN number or ID number:</u>	UN 2924
<u>14.2. UN proper shipping name:</u>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	38
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 2924
<u>14.2. UN proper shipping name:</u>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 15 of 16

Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	UN 2924
<u>14.2. UN proper shipping name:</u>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3+8
Special Provisions:	223 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	UN 2924
<u>14.2. UN proper shipping name:</u>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (propan-2-ol, Ammonia)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3+8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y342
Excepted quantity:	E1
IATA-packing instructions - Passenger:	354
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	365
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	Ammonia

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

E1 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Additional information:

P5c

Additional information

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Eriochrome black T - Buffer solution

Revision: 07.10.2025

Product code: AC15.01457

Page 16 of 16

Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1
Flam. Liq. 2: Flammable liquids, hazard category 2
Acute Tox. 4: Acute toxicity, hazard category 4
Skin Corr. 1B: Skin corrosion, sub-category 1B
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H290 May be corrosive to metals.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains 2-aminoethanol. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)