

**Platinum standard solution**

Revision: 10.06.2025

Product code: AC18.01242

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Platinum standard solution

UFI: 5APJ-2241-NWCM-5KM5

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet**

**Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
 Street: Rua de Júlio Dinis 676 7º  
 Place: N-4050-320 Porto  
 Telephone: +351 226002917  
 E-mail: info@analytichem.com  
 Contact person: SDS service department  
 E-mail: SDS@analytichem.com  
 Internet: www.analytichem.com  
 Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
 Street: Industriezone "De Arend" 2  
 Place: B-8210 Zedelgem  
 Telephone: +32 50 28 83 20  
 E-mail: info.be@analytichem.com  
 Contact person: SDS service department  
 E-mail: SDS@analytichem.com  
 Responsible Department: AnalytiChem:  
 EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
 EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
 EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
 UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
 USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
 Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
 Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333  
 +44 20 3807 3798 (CHEMTREC)

**1.4. Emergency telephone number:**

**Further Information**

No data available

## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 2 of 13

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226  
Acute Tox. 4; H332  
Acute Tox. 4; H312  
Skin Irrit. 2; H315  
Eye Irrit. 2; H319  
STOT SE 3; H335  
STOT RE 2; H373  
Asp. Tox. 1; H304  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

xylene (mix)

**Signal word:**

Danger

**Pictograms:****Hazard statements**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 3 of 13

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
	xylene (mix)			95 - < 100 %
	905-588-0	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	905-588-0	xylene (mix)	95 - < 100 %
		inhalation: LC50 = 6700 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 12126 mg/kg; oral: LD50 = 3523 mg/kg	

## Further Information

No data available

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General information

First aider: Pay attention to self-protection!

## After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

## After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

## After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

## After ingestion

Rinse mouth.

Do NOT induce vomiting. Aspiration hazard

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Observe risk of aspiration if vomiting occurs.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

**Platinum standard solution**

Revision: 10.06.2025

Product code: AC18.01242

Page 4 of 13

**Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids Vapours can form explosive mixtures with air. In case of fire, dangerous combustion gases or vapors may be released.

**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

Heating causes rise in pressure with risk of bursting.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7

## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 5 of 13

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Read label before use.  
Handle and open container with care.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Provide adequate ventilation.  
Use extractor hood (laboratory).

**Advice on protection against fire and explosion**

Take precautionary measures against static discharges.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

**Advice on general occupational hygiene**

Keep away from: Food and feedingstuffs  
When using do not eat, drink, smoke, sniff.  
Provide eye shower and label its location conspicuously  
In the immediate working surroundings there must be: Emergency shower installed

**Further information on handling**

Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Take off immediately all contaminated clothing and wash it before reuse.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.  
National regulations

**7.3. Specific end use(s)**

The product is intended for research, analysis and scientific education.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 6 of 13

## Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

## DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
	xylene (mix)			
Worker DNEL, long-term		inhalation	systemic	221 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	442 mg/m <sup>3</sup>
Worker DNEL, long-term		inhalation	local	221 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	442 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	212 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	systemic	260 mg/m <sup>3</sup>
Consumer DNEL, long-term		inhalation	local	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute		inhalation	local	260 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	12,5 mg/kg bw/day

## PNEC values

CAS No	Substance	Value
	xylene (mix)	
Freshwater		0,327 mg/l
Freshwater (intermittent releases)		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
Soil		2,31 mg/kg

## Additional advice on limit values

Observe in addition any national regulations!

## 8.2. Exposure controls

## Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

goggles

Face protection umbrella

## Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four

**Platinum standard solution**

Revision: 10.06.2025

Product code: AC18.01242

Page 7 of 13

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Wear suitable protective clothing.

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Take off immediately all contaminated clothing and wash it before reuse.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**Thermal hazards**

No data available

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	137 °C
Flammability:	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	30 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	No data available
Solubility in other solvents	
not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	not determined
Dispersion stability:	No data available No data available
Vapour pressure:	<=1100 hPa
(at 50 °C)	
Density:	0,87000 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	not determined
Particle characteristics:	No data available

**9.2. Other information****Information with regard to physical hazard classes**

Explosive properties

No data available

Sustained combustibility:

No data available

**Platinum standard solution**

Revision: 10.06.2025

Product code: AC18.01242

Page 8 of 13

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

No data available

**Other safety characteristics**

Evaporation rate:

not determined

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

not determined

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Flammable. Vapours can form explosive mixtures with air.

**10.2. Chemical stability**

Protect against: Radiant heat.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

In case of fire may be liberated:

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Harmful if inhaled.

Harmful in contact with skin.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) 1101 mg/kg; ATE (inhalation vapour) 11,01 mg/l; ATE (inhalation dust/mist) 1,502 mg/l



## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	xylene (mix)				
	oral	LD50 3523 mg/kg	Rat	Study report (1986)	EU Method B.1
	dermal	LD50 12126 mg/kg	Rabbit	Publication (1962)	Single dermal dose under occlusion follo
	inhalation (4 h) vapour	LC50 6700 mg/l	Rat	Toxicol Appl Pharmacol 33:543-558. (1975)	EU Method B.2
	inhalation dust/mist	ATE 1,5 mg/l			

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (xylene (mix))

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (xylene (mix))

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

No data available

**Further information**

No data available

**SECTION 12: Ecological information****12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	xylene (mix)					
	Acute fish toxicity	LC50	8,4 mg/l	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety. OECD Guideline 203
	Acute algae toxicity	ErC50	4,9 mg/l	72 h	Raphidocelis subcapitata	Ecotoxicology and Environmental Safety. OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 3,4	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3 other: US EPA 600/4-91-003
	Fish toxicity	NOEC mg/l	> 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve Fish were exposed in artificial streams
	Crustacea toxicity	NOEC mg/l	1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3 other: US EPA 600/4-91-003
	Acute bacteria toxicity	EC50 mg/l ( )	> 175	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 ( ) OECD Guideline 209

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
	xylene (mix)	3,2

**BCF**

CAS No	Chemical name	BCF	Species	Source
	xylene (mix)	> 5,5 - < 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

**Further information**

Do not allow to enter into surface water or drains.  
Explosion risk.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 11 of 13

**Disposal recommendations**

Send to a physico-chemical treatment facility under observation of official regulations.  
Do not allow to enter into surface water or drains.

**Contaminated packaging**

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1307
<b>14.2. UN proper shipping name:</b>	XYLENE, Gemisch
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

**Other applicable information (land transport)**

E1

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1307
<b>14.2. UN proper shipping name:</b>	1307 XYLENE, Gemisch
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Classification code:	F1
Limited quantity:	5L

**Other applicable information (inland waterways transport)**

E1

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1307
<b>14.2. UN proper shipping name:</b>	XYLENES mixture
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3
Marine pollutant:	Nein
EmS:	F-E,S-D

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1307
<b>14.2. UN proper shipping name:</b>	XYLENES mixture
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid.

**14.7. Maritime transport in bulk according to IMO instruments**

**Platinum standard solution**

Revision: 10.06.2025

Product code: AC18.01242

Page 12 of 13

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

**Additional information**

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

**National regulatory information**

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Permeates easily through outer skin and causes poisoning.

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

Flam. Liq. 3: Flammable liquids, hazard category 3

Acute Tox. 4: Acute toxicity, hazard category 4

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Irrit. 2: Skin irritation, hazard category 2

Eye Irrit. 2: Eye irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Platinum standard solution

Revision: 10.06.2025

Product code: AC18.01242

Page 13 of 13

## Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Acute Tox. 4; H312	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

## Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (auditory organs, liver, kidneys, central nervous system) through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

## Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*