

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PartiStan 2806 Calibration Fluid (150-701-001)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Canada Inc.
Street: Québec, CANADA
Place: 21800 Clark Graham Ave
CDN-H9X 4B6 Baie-D'Urfé
Telephone: +1 (800) 361-6820
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

Telefax: +1 (800) 253-5549

1.4. Emergency telephone number:

Further Information

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 2 of 12

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Carc. 1B; H350

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

"Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"

"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"

"Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified"

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.

H350 May cause cancer.

Precautionary statements

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing and eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling

Restricted to professional users.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 3 of 12

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-53-6	"Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"			60 - < 65 %
	265-156-6	649-466-00-2		
	Carc. 1B; H350			
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"			15 - < 20 %
	265-149-8	649-422-00-2		
	Asp. Tox. 1; H304			
64742-55-8	"Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified"			15 - < 20 %
	265-158-7	649-468-00-3		
	Carc. 1B; H350			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-53-6	265-156-6	"Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"	60 - < 65 %
		oral: LD50 = > 5000 mg/kg	
64742-47-8	265-149-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"	15 - < 20 %
		inhalation: LC50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-55-8	265-158-7	"Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified"	15 - < 20 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 4 of 12

4.2. Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints
Pneumonia
Vapours may cause drowsiness and dizziness.
Dizziness
Depression of central nervous system
Headache
Repeated exposure may cause skin dryness or cracking.

Dermatitis

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration hazard

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam
Carbon dioxide (CO₂)
Extinguishing powder
Water

Unsuitable extinguishing media

No data available

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂)
Carbon monoxide
Sulphur oxides
Nitrogen oxides (NO_x)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Use water spray jet to protect personnel and to cool endangered containers.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 5 of 12

Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use extractor hood (laboratory).
Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Do not breathe vapour/aerosol.
Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a place accessible by authorized persons only.
Keep container tightly closed.
Protect against: Radiant heat.

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 6 of 12

Hints on joint storage

National regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

Laboratory chemicals

Only for laboratory and analysis purposes.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
DNEL type				
64742-53-6	"Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m ³
Worker DNEL, long-term	inhalation	local		5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day
64742-55-8	"Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified"			
Worker DNEL, long-term	inhalation	systemic		2,73 mg/m ³
Worker DNEL, long-term	inhalation	local		5,58 mg/m ³
Worker DNEL, long-term	dermal	systemic		0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local		1,19 mg/m ³
Consumer DNEL, long-term	oral	systemic		0,74 mg/kg bw/day

PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-53-6	"Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"	
Secondary poisoning		9,33 mg/kg
64742-55-8	"Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified"	
Secondary poisoning		9,33 mg/kg

Additional advice on limit values

Observe in addition any national regulations!

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 7 of 12

Eye/face protection

goggles
Face protection umbrella

Hand protection

Tested protective gloves must be worn
The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.
Wash hands and face before breaks and after work and take a shower if necessary.
Draw up and observe skin protection programme.
In the immediate working surroundings there must be: Emergency shower installed

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	light red	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic: (at 40 °C)		No data available
Water solubility:		No data available
Solubility in other solvents		
No data available		
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 8 of 12

Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Heat, Radiant heat.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

in case of fire, see:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 9 of 12

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-53-6	"Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1992)	EPA OTS 798.1175
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1992)	EPA OTS 798.1100
	inhalation (4 h) vapour	LC50 > 5,28 mg/l	Rat	Study report (1987)	OECD Guideline 403
64742-55-8	"Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified"				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

May cause cancer. ("Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"; "Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified")

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 10 of 12

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

No data available

Further information

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-53-6	"Distillates (petroleum), hydrotreated light naphthenic; Baseoil - unspecified"					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"					
	Acute fish toxicity	LL50 2 - 5 mg/l	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 8,3 mg/l	72 h	Raphidocelis subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EL50 1,4 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
64742-55-8	"Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified"					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 11 of 12

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 75

Safety Data Sheet

according to Regulation (EC) No 1907/2006

PartiStan 2806 Calibration Fluid (150-701-001)

Revision: 12.11.2025

Product code: AC18.06707

Page 12 of 12

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 5,11.

Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard, hazard category 1

Carc. 1B: Carcinogenicity, hazard category 1B

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Carc. 1B; H350	Calculation method
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

H350 May cause cancer.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	PC21	-	-	21	15	-	-	-	
2	PROC15	-	-	-	15	-	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)